

CALL FOR BIDS

NOTICE is hereby given that pursuant to ARS 11-254.01, Greenlee County will receive sealed bids up to the hour of 5:00 p.m., September 2, 2026, for the furnishing of one (1) Roll-Off Truck for the Roads Department.

Specifications are available upon request from the Office of the Clerk of the Board of Supervisors located in the Greenlee County Courthouse Annex, 253 5th Street, P O Box 908, Clifton, Arizona, from 8:00 a.m. - 5:00 p.m., Monday - Thursday, 928-865-2072 or at www.greenlee.az.gov

All bids must be marked **"BID ON Roll-Off Truck – Roads Department"** on the outside of the sealed envelope containing the same and addressed to the Greenlee County Board of Supervisors, P O Box 908, Clifton, Arizona, 85533. Bids will be opened on Thursday, September 3, 2026, at 10:00 a.m. and presented to the Board of Supervisors at the next scheduled meeting. The Board of Supervisors reserves the right to reject any and all bids or to extend the award date. Bidders are in competition with procurement agencies including the state procurement agency.

Dated this 10th day of August 2026.

/s/ Bianca Castañeda
Clerk of the Board

Request for Proposals: New Roll-Off Truck

Issued by: _____ |

| Issue Date: _____ | Proposal Due Date: _____

1. Purpose and Overview

Greenlee County is requesting sealed proposals from qualified vendors for the purchase and delivery of one new, current model year or newer tandem-axle roll-off truck equipped with a roll-off hoist, hydraulic system, automatic tarping system, lighting, safety equipment, manuals, warranty coverage, and all standard equipment necessary for immediate municipal or public works service.

2. Bid Format and Submission Requirements

1. Proposals shall be submitted in a sealed envelope clearly marked: "Proposal for New Roll-Off Truck."
2. Proposals must include one original and one copy.
3. Late proposals may be rejected and returned unopened.
4. The person signing the proposal must have authority to bind the vendor to the terms, pricing, delivery schedule, and warranty offered.
5. All pricing shall be firm and shall include freight, delivery, dealer preparation, required inspections, title documents, and all equipment specified in this RFP.
6. Vendors shall provide a completed specification compliance form identifying "Comply," "Exception," or "Alternate" for each major technical requirement.
7. Any exceptions must be clearly identified with supporting documentation. Failure to identify exceptions may be considered full compliance.
8. Greenlee County reserves the right to reject any or all proposals, waive minor irregularities, request clarification, and award in the best interest of the County.

3. Minimum Chassis Specifications

Item	Minimum Requirement
Model Year	New, current model year or newer.
GVWR	Minimum 66,000 lb gross vehicle weight rating, tandem rear axle configuration.
Cab Configuration	Conventional cab, single cab, left-hand drive, air conditioning, heater/defroster, tilt/telescoping steering wheel, high-back air ride driver seat, passenger seat, AM/FM or equivalent radio, backup alarm, and standard safety equipment.

Engine	Diesel engine, minimum 9-liter class, minimum 350 horsepower and 1,150 lb-ft torque or approved equivalent, compliant with applicable emissions regulations.
Transmission	Heavy-duty automatic transmission suitable for severe-duty refuse/public works service, Allison 4500 RDS or approved equivalent, with PTO provision.
Frame	Heavy-duty steel frame with full reinforcement or liner as required by body manufacturer; frame strength suitable for roll-off operation and hoist rating.
Axles and Suspension	Front axle minimum 14,000 lb; rear tandem axle minimum 46,000 lb; suspension rated for GVWR and roll-off service.
Brakes	Full air brake system with ABS, automatic slack adjusters, spring parking brakes, air dryer, and moisture ejectors as standard.
Fuel Tank	Minimum 70-gallon usable capacity, aluminum or steel, mounted to provide clearance for roll-off body and hydraulic equipment.
Wheels and Tires	Heavy-duty steel or aluminum wheels with tires rated for axle capacities and intended service.

4. Roll-Off Hoist and Body Specifications

Item	Minimum Requirement
Hoist Capacity	Minimum 60,000 lb rated roll-off hoist capacity.
Container Compatibility	Compatible with standard outside-rail roll-off containers up to 22 feet long and municipal refuse, debris, and bulk material applications.
Hoist Frame	Heavy-duty structural steel main frame, minimum 8 in. x 4 in. x 1/2 in. tubing or manufacturer-approved equivalent.
Subframe	Structural steel subframe designed for the chassis, hoist capacity, container length, and severe-duty application.
Hydraulic Cylinders	Double-acting lift and reeving cylinders sized for rated capacity; pins, bushings, and hinge points shall be greasable and serviceable.
Cable System	Minimum 7/8 in. hoist cable with forged or cast cable end, suitable sheaves, cable anchor, and replaceable wear components.
Controls	Inside cab controls and outside controls, clearly labeled and protected from accidental operation.
Container Locks	Automatic or hydraulic container locks and rear hold-downs suitable for standard containers.
Rollers	Rear and side rollers with replaceable pins and bushings; rollers shall be greaseable and designed for heavy-duty container loading.
ICC/DOT Bumper	Fold-up or stowable ICC bumper compliant with applicable regulations and compatible with roll-off operation.

5. Hydraulic, Tarping, Electrical, and Safety Equipment

- Hydraulic pump shall be direct-mounted or PTO-driven and properly matched to the hoist system.

- Hydraulic reservoir shall be minimum 50 gallons or as recommended by the hoist manufacturer, with suction screen, return filtration, breather, and sight/temperature gauge.
- System shall include pressure relief protection, weather-protected hose routing, and serviceable hydraulic fittings.
- Automatic tarping system shall be included, sized for containers up to 22 feet, with in-cab or protected outside controls.
- LED lighting package shall include stop, tail, turn, marker, clearance, backup, license plate, and work lights as required.
- Safety equipment shall include backup alarm, hoist-up alarm, in-cab warning light, reflective conspicuity tape, mud flaps, fire extinguisher, safety triangles, and all federally required equipment.
- Paint shall be manufacturer standard white unless otherwise specified by Greenlee County.

6. Manuals, Warranty, Training, and Delivery

1. Vendor shall provide operator manuals, service manuals, parts manuals, warranty documents, and build sheets for the chassis, hoist, tarp system, and installed equipment.
2. Minimum warranty shall include manufacturer standard chassis warranty, engine warranty, transmission warranty, and not less than one year on the roll-off hoist, tarp system, hydraulics, and workmanship.
3. Vendor shall provide on-site orientation or training for operators and maintenance staff at delivery, including safe hoist operation, tarp use, inspections, and routine maintenance.
4. Delivery shall be FOB destination to: 606 County Airport Road Duncan AZ. Vendor shall state guaranteed delivery time after receipt of purchase order.
5. The truck shall be delivered fully assembled, serviced, fueled, inspected, titled as applicable, and ready for immediate operation.

7. Required Vendor Response

- Completed proposal signature page.
- Detailed price quotation including base unit, options, freight, delivery, title, and any applicable fees.
- Specification compliance sheet with exceptions clearly noted.
- Manufacturer build sheets for chassis, hoist, tarp system, and major installed components.
- Warranty summary and service contact information.
- Delivery schedule after receipt of order.

9. Proposal Signature Page

Vendor Name: _____

Total Proposal Price: \$_____

Delivery Time: _____

Make: _____

Model: _____

Year: _____

Authorized Signature: _____ Date: _____